



**Compact Type
Electrochemical Workstation
ZSTAT800m**

Including Internal FRA
10Volts/800mA
Full Software Package Included

*For
Corrosion
Material Testing
Sensor/BioElectrochemistry
Battery/Fuel Cell
Super Capacitor/Solar Cell*

Electrochemical Workstation ZSTAT800m

The ZSTAT800m is an outstanding Potentiostat/Galvanostat/FRA offered at affordable price. This powerful model is a perfect choice for the complete DC and impedance characterization of various electrochemical applications.

The ZSTAT800m is equipped with a frequency response analyzer(FRA) for system as standard and it provides high performance impedance measurements over the frequency range 10uHz to 1MHz. Our (4) advanced software packages, which are categorized by application field, are provided with the system as standard. Consequently, it widens ZSTAT800m's flexibility.


Features

- Economical high quality Potentiostat/Galvanostat/Impedance analyzer
- Compact size with full functions
- Wide current ranges(8uA~800mA) for various applications
- Built-in FRA: enables EIS tests by using software
- 18 EIS techniques capability including multisine & real time EIS
- Main applications
 - Corrosion, general electrochemistry, sensor, battery, fuel cell, supercapacitor, solar cell, etc.
- Current interrupt IR measurement
IR compensation (dynamic, positive feedback)
- Voltage pulse or current pulse charge/discharge test(GSM,CDMA etc.), sine wave function for ripple simulation in battery test package & pulse plating available
- High speed data sampling time
 - 2usec or 3usec depending on data point number
- Fast sweep mode (5000V/sec with 10mV data sampling)
- 3 measurement/control voltage ranges & 6 measurement/control current ranges
- Internal 542,000 data point storage & continuing experiment regardless of PC failure.
- Full software package included as standard
 - Corrosion test software package (COR)
 - EIS test software package (EIS)
 - Electrochemical analysis software package (EAS)
 - Energy software package (BAT)
- Multichannel configuration available
- Free software upgrade

Application

The ZSTAT800m electrochemical workstation is ideal for fundamental research in electrochemistry, development and quality assurance of new sensors, corrosion/coatings, electrode material, membrane, conducting polymer, evaluation power device research such as battery materials, fuel cells, super capacitors and solar cells.

■ General Electrochemistry




The ZSTAT800m is also suitable for the development of bio-research, electron transfer kinetic studies or electrochemical analysis of compounds.

■ Batteries



The system is very well adapted for researches on the cycling behavior of battery. It supports EVS(electrochemical voltage spectroscopy)/ GITT/PITT test. Fast pulse capability for GSM, CDMA test is included in battery test software package. Pulse profile measurement function to check pulse shape is available. For ripple simulation test, sine wave charging/discharging is available.

■ Solar Cells



Solar cell development and production require extensive material and device testing to improve efficiency and match individual cells for panel construction. The ZSTAT800m is the best solution for photovoltaic cell characterization.

■ Corrosion



The system is suitable for measuring low corrosion rates and EIS test to evaluate corrosion.

■ Sensors




The ZSTAT800m can be used for sensor research using with DNA chips or screen printed electrodes. System's minimum current range is 800nA(with gain). Cyclic voltammetry, Chronoamperometry and EIS measurement can be used for this application.

■ Super Capacitors



The ZSTAT800m has fast potentiostat circuit with high speed data acquisition. This function is well applicable to super capacitors testing. Charging/discharging capability is used for this application



ZSTAT800m front view



ZSTAT800m rear view

Fuel Cells



The ZSTAT800m is ideal for characterizing the fuel cells and anodic/cathodic process mechanism at development and research grade. This system can be directly used for PEMFC, DMFC, and DEFC etc. Automatic current ranging potentiostatic/galvanostatic IV curve is available.

Smart Manager(SM) Software

The Smart Manager(SM) provides user defined sequential test by using sequence file, technique menu and batch file. The batch file allows the users to do a serial test by combining sequence files and/or technique files.


The SM software is easy to use and supports various electrochemical experiments including functions of system control, schedule file editor, real time graph, analysis graph, user calibration, and data file treatment etc.

Each software package's upgrade will be provided at free of charge.

Basic software function

Value of Interest real time display


- User defined aux signal definition & data treatment.
- Major parameters display selection




Data file export: ASCII or Excel format

Basic Technique with Standard Functions


- 1) Potentiostatic
- 2) Galvanostatic
- 3) Double step potentiostatic
- 4) Double step galvanostatic
- 5) OCP measurement
- 6) Potential sweep
- 7) Current sweep
- 8) Cyclic voltammetry
- 9) Fast potential sweep
- 10) Potentiostatic Ru measurement
- 11) Galvanostatic Ru measurement



50 usec data sampling



DC graph



Peak find module

The above functions can be used sequentially by step control function.

Sequence Editor

User can design his/her own experiment procedure by using TASK sequential routine editor.



1) Control Task Parameter

Control Mode			
constant	GSTAT	constant current control	
	Crate	constant Crate control	
	PSTAT	constant voltage control	
	POWER	constant power control	
	LOAD	constant load control	
	CC-CV	constant current constant voltage control	
	Crate-CV	crate constant voltage control	
	CP-CV	constant power constant voltage control	
	CL-CV	constant load constant voltage control	
	Id	Id control	
	Is	Is control	
	OCP	OCP control	
	Step	GSTAT	current step control
		PSTAT	potential step control
Sweep	GSTAT	current sweep control	
	FAST-G	fast current sweep control	
	PSTAT	potential sweep control	
	FAST-P	fast potential sweep control	
	ACV	AC voltammetry	
EIS	GSTAT	galvanostatic EIS	
	PSTAT	potentiostatic EIS	
	OCP	OCP EIS	
	PSEUDO	pseudo galvanostatic EIS	
	HFR G	galvanostatic HFR	
	HFR P	potentiostatic HFR	
	M sineG	galvanostatic multisine EIS	
	M sineP	potentiostatic multisine EIS	
	RTIG	galvanostatic real time EIS	
	RTIP	potentiostatic real time EIS	
	Rest	rest control	
ZRA	ZRA control		
Loop	loop control		
Pulse	Vpulse	voltage pulse control	
	Ipulse	current pulse control	
	GSINE	current sine wave control	
	PSINE	potential sine wave control	

- Constant potential, current, C-rate, power, load, OCP
- Sweep potential, current
- Fast sweep potential, current
- Staircase potential, current
- CC-CV, CP-CV, CL-CV, Crate-CV control
- Id, Is control
- EIS control
- Pulse or sinewave control
- Rest (voltage monitoring only)
- Loop(cycle) control

2) Cut-off(Vertex) condition

- Time (step, test, loop, cycle)
- Current, current density
- Voltage
- Capacity
- C-rate
- -dV
- |dV/dt|
- |dl/dt|
- Eoc
- etc.

List	Item	Cond
1	Step Time	>
2	None	OP
3	Step End	>
4	Step Time	>
5	Current	>
6	Density	>
7	Voltage	>
8	dV/dt	>
9	dl/dt	>
10	Temp (C)	>
11	AUX1	>
12	AUX2	>
13	AUX3	>
14	Test Time	>
15	Loop Time	>
16	Cycle Time	>
17	Eoc	>
18	Energy(Wh)	>
19	LCCP%	>
20	LCCD%	>
21	FCCP%	>
22	FCCD%	>
23	Power(W)	>
24	Sum(QAh)	>
25	SumE(Wh)	>
26	D IN	>
27	Crate	>
28	dV	>
29	dV/dt	>
30	Err T	>
31	End	>

Cut-off Condition

3) Sampling Condition


- time, |dl/dt|, |dV/dt|, burst time

4) Flow View

This displays sequence flow at a glance.

Batch Function

User can design batch file including multiple technique files and/or sequence files. With this batch file, user can experiment several techniques/sequence in series automatically.




Advanced Software Packages

For a wide range of application, following software packages are provided as standard.


■ EIS Software Package (EIS)

- | | |
|-----------------------------|-------------------------------------|
| 1) Potentiostatic EIS | 9) Potentiostatic HFR monitor |
| 2) Galvanostatic EIS | 10) Galvanostatic HFR monitor |
| 3) Pseudo galvanostatic EIS | 11) Multisine potentiostatic EIS |
| 4) OCP(*1) EIS | 12) Multisine galvanostatic EIS |
| 5) Potentiodynamic PEIS | 13) Intermittent potentiostatic EIS |
| 6) Galvanodynamic GEIS | 14) Intermittent galvanostatic EIS |
| 7) Potentiodynamic HFR | 15) Real time potentiostatic EIS |
| 8) Galvanodynamic HFR | 16) Real time galvanostatic EIS |


(*1) The system measures open circuit potential before each frequency change and applies AC sine wave on this potential.




OCV EIS



Potentiodynamic PEIS



Rs, Cp & Idc vs Vdc plot




Coin Cell Intermittent PEIS
3D Nyquist Plot By ZMAN


■ Energy Software Package (BAT)

BAT software supports IR measurement.

- Battery Test Technique
 - CC/CV test for cycle life test of lithium battery
 - CC/CC test for cycle life test of NiCd & NiMH battery
 - Discharging test
 - EVS (Electrochemical voltage spectroscopy)
 - Variable scan rate CV
 - Potentiostatic IV curve
 - Galvanostatic IV curve
 - Steady state CV
 - GITT
 - PITT
 - Pulse mode is available for GSM & CDMA profile.
- Pulse shape profile can be measured by user's demand.




CC/CV test



EVS



Pulse shape profile monitor
(micro sec order)



Current sine wave
(charge ripple simulation)

2) Control Mode


- Charge: CC, CC-CV, pulse, sine wave
- Discharge: CC, CP, CR, pulse, sine wave

- Cutoff Condition
 - Time, voltage, current, power, auxV etc.


Various battery charge/discharge test is available including pulse discharge for GSM, CDMA application.

■ Electrochemical Analysis Software Package (EAS)


- Step Techniques
 - CA (Chronoamperometry)
 - CC (Chronocoulometry)
 - CP (Chronopotentiometry)
- Sweep Techniques
 - LSV (Linear Sweep Voltammetry)
 - SDV (Sampled DC Voltammetry)
 - Fast CV
 - Fast LSV
 - AC voltammetry
- Pulsed Techniques
 - DPV (Differential Pulse Voltammetry)
 - SWV (Square Wave Voltammetry)
 - DPA (Differential Pulse Amperometry)
 - NPV (Normal Pulsed Voltammetry)
 - RNPV (Reverse Normal Pulse Voltammetry)
 - DNPV (Differential Normal Pulse Voltammetry)



50 usec sampling



sdv_charging/sdv_discharging




NPV & RNPV overlay


■ Corrosion Software Package (COR)

Corrosion technique supports IR compensation.


- Tafel (Tafel experiment)
- Rp (Polarization resistance)
- Potentiodynamic
- Galvanodynamic
- Cyclic polarization
- Ecorr vs. time
- RpEc trend
- Reactivation potential
- Critical pitting potential
- Potentiostatic ECN
- Galvanostatic ECN



Cyclic polarization resistance



Tafel plot



Polarization resistance

Control & Real Time Graph

Smart Manager program provides virtual control panel for control & data acquisition with real time graph.




Multichannel real time graph

User can control and monitor in this control panel and he/she can monitor data in VOI(Value Of Interest) window and channel status in one window. Real time graph's X Y axis format will be changed per technique automatically. It can be defined by user's demand per technique. For experiment

using sequence file or batch file, user can designate X, Y axis parameter on three different real time graph.

Each real time graph format can be also selected. Real time graph and VOI will be changed depending on DC test or impedance test automatically. Virtual control panel always displays the graph for recent test result. For impedance measurement, wave monitor will be displayed on real time graph to check wave's quality. This monitor can be switched to Lissajous(I vs. E) plot.




Single channel control panel



Multichannel real time graph

Strip Chart





Strip chart recorder function allows you to monitor DC curve in real time. You can monitor 2 Y axis data such as voltage, current, auxV, power, capacity, etc., in real time.

Graph



Smart Manager's graph function is to simplify the operation. There are 3 kinds of graph per each experiment. You can change X, Y1, Y2, Y3, Y4 axis parameter as you want. Each graph provides shortcut buttons. When you click these buttons, the format of the graph will be changed accordingly.




: value divided by weight

In DC and Cycle graph, whenever you click or the parameters which are related to current such as current, capacity, energy, power, load, etc., are changed into calculated specific value or density value, respectively.

: value divided by active area





1) DC Graph

- For general data display
- 4 shortcut buttons: I vs. V, E vs. LogI, V, I vs. time, V vs. Q
- Graph parameters: Time, Eref, I, Eoc, Id, LogI, Load, ChQ, DchQ, ChQs, DchQs, Ch P, Dch P, Ch-Wh, Dch-Wh, Sum Wh, Sum Q, Sum |Q|, |Q|, Rp, dQ/dV



2) EIS Graph



- For EIS data display
- 3 shortcut buttons: Nyquist plot, Bode plot, Cs vs. frequency
- Graph parameters: Frequency, Zre, -Zim, Zmag, Zph, Y, Yimag, Y, |Y|, Yph, LogZ, LogY, Rs(R-C), Cs(R-C), Rp(R|C), Cp(R|C), Rs(R-L), Ls(R-L), Q(R-L), time, Vdc, Idc




3D Bode Plot by ZMAN
Technique used: Potentiodynamic impedance measurement by using a corrosion cell

3) BAT Graph


- For battery cycle data display
- 3 shortcut buttons: cycle capacity, cycle average, Log(cycle No) vs. depth of discharge plot.
- Graph parameters: cycle number, Ch Q, Dch Q, Sum Q, Coulomb Eff, Ch-Wh, Dch-Wh, Sum Wh, Energy Eff, MinV, MaxV, ChQs, DchQ, ChVavg, DchVavg, Vavg




Data Export to ASCII & Excel File



Selectable between 'Convert data on graph only' and 'Convert selected file(s)'



3D Bode plot for series measurement




Parameter plot

Data Analysis Software

ZIVE data file can be used for analysis by using external IVMAN™ software for DC analysis, IVMAN DA™ software for battery data analysis, IVMAN PA™ software for photovoltaic cell data analysis and ZMAN™ software for EIS data analysis without license.

ZMAN™ EIS Data Analysis Software


- Model simulation and fitting
- 2D- and 3D-Bode and Nyquist plots
- Automatic equivalent circuit model search function
- Project concept to handle multiple EIS data analysis
- Parameter plot from fitted elements value
- Compatible with data format from Zahner, Gamry, Ametek, etc. (License code is needed.)
- Various weighting algorithm
- Model library and user model
- KK plot
- Batch fitting for project data
- Impedance parameter simulation
- Interpolate bad data
- Black-Nichols plot
- 3D graph setting option
- Improved model editor
- Application model library for automatic searching
- Parameter simulation of model
- Genetic algorithm option for initial guessing
- Automatic initial guessing
- Trace movie function on fitting
- Free for ZIVE's data format(*.seo, *.wis) analysis (No license code required.)
- Circle fitting
- Data editing available (insert, delete, edit)
- Add/subtract element parameters
- Add/subtract model parameters
- Impedance, Z in polar, admittance, Y in Polar, modulus, M in polar, dielectric constant, E in polar. data display
- Empty cell capacitance calculation
- Find file function
- Data replacement by formula function
- Cursor data display
- Model finding result automatic sorting by Chi square value
- R, C R, L R, Q preview & graphic
- ZHIT function
- Mott-Schottky analysis
- Donor density vs. Vfb graph
- C vs. voltage graph




Importing 3rd parties ASCII data file




Project manager with data preview





Cursor data display




Data replacement by formula function




Fitting display



Model editor & model library




Automatic model searching




LEVM fitting


Electrochemical Workstation ZSTAT800m



Parameter simulation




Element add/subtraction




C/R-V graph




Finding data file menu



Circular fitting






Bode & Nyquist overlay & 3D plots




2D Nyquist plot




2D Bode plot




Rp, Cp vs. frequency (R|C)




Empty cell capacitance



Donor density vs. Vfb graph and analysis



KK consistency



Mott-Schottky analysis window

IVMAN™ DC Data Analysis Software




- IVMAN™ software package consists of
- IVMAN software
 - IVMAN utilities
 - IVMAN differential analysis software
 - IVMAN photovoltaic cell analysis
 - IVMAN Tafel analysis
 - IVMAN extractor
 - IVMAN peak find module




IVMAN DA™ Battery Test Data Analysis Software

- Battery test data analysis
- Electrochemical voltage spectroscopy (dQ/dV vs. V)
- Voltage vs. Capacity analysis (V vs. Q)
- Cycle graph (Q vs. cycle)
- Differential voltage graph (dV/dQ vs. Q)




Measured data




V vs. Q

Electrochemical Workstation ZSTAT800m




Cycle graph

dQ/dV vs. V




dV/dQ vs. Q

Export ASCII file




Polarization resistance fitting

Polarization analysis result




Time graph

Find peak menu



CV graph

3D graph




Edit data menu

Universal graph



IVMAN™ Photovoltaic Cell Analysis




- Automatic analysis of parameters
- : open circuit voltage, open circuit current, max. power, efficiency, photo induced current, diode quality factor, series resistance, etc.




IVMAN TA™ Tafel Analysis

- Simple Tafel calculation




IVMAN EX™ Extractor

- Extracting data by cycle number or step
- Exporting ASCII file



IVMAN PF™ Peak Find Module

- Independent peak finding software



IVMAN™ Main Software

- Ideal for DC corrosion data analysis and electro-analytical data analysis
- Initial guessing function on Tafel analysis
- Polarization resistance fitting
- 3D graph
- Find peak function
- Interpolation, differentiation, integration, etc.
- Reporting function

Optional Accessories

- Battery Jig & Clamp cable



Corrosion cell kit



Flat cell kit



Permeation cell kit



Plate test cell



Plate test cell



Universal electrode holder



Black box for photo-electrochemistry




Photo-electrochemical cell



Faradaic cage




Flat specimen holder




Copper alligator electrode holder




Pt plate electrode



K type thermocouple



Single cell hardware fixture
 - for PEMFC and DMFC
 - max. temp. : 120°C or 180°C
 - active area : 5,25 cm²
 - MEA is not included.



Membrane conductivity cell

Specification

Main System	
PC communication	USB2.0 high speed
Line voltage	100~240VAC, 50/60Hz, 1Amp
Power adapter	24V 2.5Amp
Size/weight	160 x 319.4 x 57.9mm(WxDxH) / 1.9Kg
Max. output power	9.6Watt (12V@0.8A)

System	
Cell cable	1 meter shielded type (standard) working, reference, counter, working sense
Control DAC	DSP with FPGA 2x16bit DAC(50MHz) for bias & scan
Data acquisition ADC	2x16bit ADCs(500kHz) for voltage, current
Calibration	Automatic
Filter selection	4ea (5Hz, 1kHz, 500kHz, 5MHz)
Scan rate	0~200V/sec in common mode 0~5000V/sec in fast mode
Max. channel No.	8 channels via USB connection
Front panel LED	RUN, CELL ON
Internal data memory	542,000 points

Power Amplifier(CE)	
Compliance voltage	±12V
Max. current	±0.8A
Control speed selection	4ea
Bandwidth	2MHz
Slew rate	10V/usec

Potentiostat Mode (voltage control)	
Voltage control	
Control voltage range	±10V, ±1V, ±100mV
Voltage resolution	16 bit per each range
Voltage accuracy	±0.02% f.s (gain x1)
Max. scan range	±10V vs. ref. E
Current measurement	
Current range	6 ranges (auto/manual setting) 8uA ~ 800mA 800nA with gain
Current resolution	16 bit 24uA, 2.4uA, 240nA, 24nA, 2.4nA, 240pA (24pA with gain)
Current accuracy	±0.05% f.s. (gain x1)

Galvanostat Mode (current control)	
Current control	
Control current range	Max. ±800mA ± full scale depending on selected range
Current resolution	16 bit 24uA, 2.4uA, 240nA, 24nA, 2.4nA, 240pA (24pA with gain)
Current accuracy	±0.05% f.s. (gain x1)
Voltage measurement	
Voltage range	10V, 1V, 100mV
Voltage resolution	16 bit 0.3mV, 30uV, 3uV
Voltage accuracy	±0.02% f.s (gain x1)

Electrometer	
Max. input voltage	±10V
Input impedance	10 ¹³ Ω
Bandwidth	>22MHz
CMRR	>114dB

EIS(Internal FRA) for System	
Frequency range	10uHz~1MHz
Frequency accuracy	0.01%
Frequency interval setting (Point / Decade)	Max. 1000/decade (<43mHz) Max. 5000/decade (>43mHz)
Amplitude	0.1mV~5V rms (Potentiostatic) 0.1~70% f.s. (Galvanostatic)
Mode	Static EIS: Potentiostatic, Galvanostatic, Pseudogalvanostatic, OCP Dynamic EIS: Potentiodynamic, Galvanodynamic Fixed frequency impedance: Potentiostatic, Galvanostatic, Potentiodynamic, Galvanodynamic Multisine EIS: Potentiostatic, Galvanostatic Intermittent EIS: Potentiostatic, Galvanostatic Real time EIS: Potentiostatic, Galvanostatic

Software	
Max. step per experiment	1000
Shutdown safety limits	Voltage, Current, Power
Max. sampling rate	2usec or 3usec depending on data point number
Min. sampling time	Unlimited
Sampling condition	Time, dV/dt dI/dt, etc.

PC Requirement	
Operating system	Windows 7/8/10/11 (32bit/64bit OS)
PC specification	Pentium4, RAM 1GB or higher
Display	1600x900 high color or higher
USB	High speed 2.0

General	
Dummy cell	One external dummy cell included
Impedance analysis S/W	ZMAN™ software
DC data analysis S/W	IVMAN™ software package

The specifications are subject to change without notice.
Windows is a registered trademark of Microsoft Corporation.


Designed by

ZIVE LAB
www.zivelab.com



WonATech Co., Ltd.
7, Neunganmal 1-gil, Seocho-gu,
Seoul, 06801, Korea
Phone: +82-2-578-6516
Fax: +82-576-2635
e-mail) sales@wonatech.com
website: www.wonatech.com

Local Distributor



ISO 9000 & ISO 14000 Qualified